

## Inch Series Deep Groove Ball Bearing



Parte No.	Diâmetro interno		Diâmetro externo		Largura (B)			
	milímetros	polegada	milímetros	polegada	Tipo aberto (mm)	Tipo aberto (polegadas)	Tipo de escudo (mm)	Tipo de escudo (polegadas)
1601	4.762	0.1875	17.462	0.6875	6.35	0.25	7.938	0.3125
1602	6.35	0.25	17.462	0.6875	6.35	0.25	7.938	0.3125
1603	7.938	0.3125	22.225	0.875	7.144	0.2813	8.731	0.3437
1604	9.525	0.375	22.225	0.875	7.144	0.2813	8.731	0.3437
1605	7.938	0.3125	23.019	0.9063	7.938	0.3125	7.938	0.3125
1606	9.525	0.375	23.019	0.9063	7.938	0.3125	7.938	0.3125
1607	11.112	0.4375	23.019	0.9063	7.938	0.3125	7.938	0.3125
1608	9.525	0.375	28.575	1.125	9.525	0.375	9.525	0.375
1609	11.112	0.4375	28.575	1.125	9.525	0.375	9.525	0.375
1610	12.7	0.5	28.575	1.125	9.525	0.375	9.525	0.375
1611	11.112	0.4375	34.925	1.375	11.112	0.4375	11.112	0.4375
1612	12.7	0.5	34.925	1.375	11.112	0.4375	11.112	0.4375
1613	14.288	0.5625	34.925	1.375	11.112	0.4375	11.112	0.4375
1614	15.875	0.625	34.925	1.375	11.112	0.4375	11.112	0.4375
1615	15.875	0.625	41.275	1.625	12.7	0.5	12.7	0.5
1616	19.05	0.75	41.275	1.625	12.7	0.5	12.7	0.5
1617	15.875	0.625	44.45	1.75	12.7	0.5	12.7	0.5
1618	19.05	0.75	44.45	1.75	12.7	0.5	12.7	0.5
1619	19.05	0.75	50.8	2	14.288	0.5625	14.288	0.5625
1620	22.225	0.875	50.8	2	14.288	0.5625	14.288	0.5625
1621	25.4	1	50.8	2	14.288	0.5625	14.288	0.5625
1622	28.575	1.125	63.5	2.5	15.875	0.625	15.875	0.625
1623	31.75	1.25	63.5	2.5	15.875	0.625	15.875	0.625
1624	31.75	1.25	65.087	2.5625	17.462	0.6875	17.462	0.6875
1625	33.337	1.3125	65.087	2.5625	17.462	0.6867	17.462	0.6875
R2	3.175	0.125	9.525	0.375	3.969	0.1563	3.969	0.1563

### Inch Series Deep Groove Ball Bearing

R2A	3.175	0.125	12.7	0.5	4.366	0.1719	4.366	0.1719
R3	4.762	0.1875	12.7	0.5	3.969	0.1563	4.978	0.196
R4	6.35	0.25	15.875	0.625	4.978	0.196	4.978	0.196
R4A	6.35	0.25	19.05	0.75	5.556	0.2187	7.144	0.2813